19 | SOLAR POWERED LAMP





RM-1

ELECTRICAL PARAMETERS

3.7V

3200mAh

LED RGB / LED WHITE³

7lm / 2500mcd

620-630nm

465-475nm

6500K

100kN

3.2mm

Ø110x48

100g

- rated voltage
- accumulator capacity¹

OPTICAL PARAMETERS

- light emitter
- max. light flux
- wavelength LED RED color
- wavelength LED GREEN color 520-535nm
- wavelength LED BLUE color
- CCT LED WHITE color²


MECHANICAL PARAMETERS

•	compressive	strength
	0011101000170	ouchgui

- projection (max.)
- housing material POLYCARBONATE
- IP protection IP67
 sealing POLYURETHANE
- size
- net weight

OPERATING PARAMETERS

 operation mode 	STEADY / FLASHING		
 on/off level³ 	150Lux / 370Lux		
 operating temperature 	-30°C to +60°C		
 max. operating time 	2000h		
 Min. charging 			
sunny / cloudy day ⁴	1h / 3h		







					("
RM110C3200LWN	5905669866521	RGB	3200mAh	-	-
RM110W3200LWN	5905669866538	WHITE	3200mAh	-	-
RM119C3200LWS	5905669866545	RGB	3200mAh	ISM 868MHz	YES
RM110W3200LWS	5905669866552	WHITE	3200mAh	ISM 868MHz	YES

The product is fully Polish - design and production. Marker road ISOLAREX - represents a new range of products representing a breakthrough in terms of the traffic sign systems. The product was developed based on years of experience using the latest technology and materials, environmentally safe, recyclable processing.

When using markers ISOLAREX high intensity of the emitted light LED can significantly increase the visibility of road markings especially in difficult weather conditions. The driver is able to see the course of the road over a distance of up to 1000 m, this means that when driving at 100 km / h, the time, the reaction of the driver is significantly extended, which obviously affects the increase driving comfort and safety. This affects

the reduction of accidents especially at night. Many drivers, thanks to this solution, he feels much more confident on the road. Active lighting ISOLAREX remains visible in all road conditions.

Application:

Highway, highways, roads, national roads, provincial roads, parking lots, bike paths, airports, driveways, ramps to the hotels and boarding houses, public buildings.

Specifications are subject to change without notice. Errors and omissions are possible. Typical given the technical parameters are statistical values, which may differ from the actual technical parameters of individual products. Special-purpose product, not suitable for room illumination and accent lighting.

1 - Capacity of the battery can be ordered individually.

2 - Color temperature can be individually ordered
3 - Level on / off. It can be individually set.
4 - The product is fully charged and ready to use.